

➔ 3105 CENTRALIZED OFFICE SHREDDER WITH AUTOMATIC OILER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | automatic oil injection insures optimal performance at all times | wide, 12" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs (strip- and cross-cut models) | super micro-cut (SMC) model meets all NSA/CSS specifications and is DOD approved | lifetime warranty on the cutting shafts (strip- and cross-cut models) | 1 year warranty on SMC cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy chain drive and dust-proof gear box housing | high quality wooden cabinet mounted on casters | convenient shred bin | 36 gallon shred volume

Dimensions (D x W x H): 23 x 22 x 40 inches, Shipping weight: 324 lbs.



20 amp. dedicated line required



CAPACITY INDICATOR



"ECC" (Electronic Capacity Control) indicator monitors capacity levels during operation.

➔ 3105 STRIP-CUT

Strip width 1/4"
Sheet capacity 50-52*
Security level 2
Feed opening 12"
Max. horsepower 2 1/2

➔ 3105 CROSS-CUT

Particle size 3/16" x 1 1/2"
Sheet capacity 30-32*
Security level 3
Feed opening 12"
Max. horsepower 2 1/2

➔ 3105 CROSS-CUT

Particle size 3/32" x 5/8"
Sheet capacity 18-20*
Security level 4
Feed opening 12"
Max. horsepower 2 1/2

* may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 3/2011.