

## DESTROYIT 4002 CENTRALIZED PAPER SHREDDER

“SPS” (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; “Easy Switch” control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating; “ESM” (Energy Saving Mode) after 1 hour of inactivity □ automatic start and stop controlled by photo cell □ “ECC” (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process □ wide, 16" feed opening □ high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs □ lifetime warranty on the cutting shafts □ quiet and powerful single phase motor rated for continuous operation □ sturdy “twin drive system” with dust-proof gear box housing □ high quality wooden cabinet mounted on casters □ convenient shred bin □ 44 gallon shred volume

Dimensions (D x W x H): 23 ¼ x 25 ¼ x 38 ¼ inches, Shipping weight: 239 lbs. (strip-cut) / 240 lbs. (cross-cut).



### EASY SWITCH



Oversized, multifunction control element uses integrated optics to indicate operational status.

### CONVENIENT SHRED BIN



A large capacity shred bin makes bags optional.

### 4002 STRIP CUT

Strip width	1/4" (6 mm)
Sheet capacity	32-35*
Security level	2
Feed opening	16"
Max. horsepower	1 ¾

### 4002 CROSS CUT

Particle size	3/16" x 1 ½" (4 x 40 mm)
Sheet capacity	24-26*
Security level	3
Feed opening	16"
Max. horsepower	1 ¾

### 4002 ALT. CROSS CUT

Particle size	3/32" x 5/8" (2 x 15 mm)
Sheet capacity	14-16*
Security level	4
Feed opening	16"
Max. horsepower	1 ¾

\* may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 5/2011.