



GXP1630

A Small Business Gigabit IP Phone

The GXP1630 is a powerful IP phone for small-to-medium businesses (SMBs). This Linux-based model includes 3 lines, 3 XML programmable soft keys, 8 BLF keys and 4-way conferencing. A 132x64 backlit LCD screen creates a clear display for easy viewing. Additional features such as dual switched gigabit network ports, HD audio, multi-language support, integrated PoE and call-waiting allow the GXP1630 to be a high quality, versatile and dependable office phone.



3 lines, 3 SIP accounts, 3 call appearances, 3 softkeys



Dual-switched auto-sensing 10/100/1000mbps network ports



Includes 8 dual-colored BLF/speed dial keys



Built-in PoE to power the device and give it a network connection



HD audio to maximize audio quality, full-duplex speakerphone



Use with Grandstream's UCM series of IP PBXs for Zero Config provisioning



Electronic Hook Switch (EHS) support for Plantronics headsets



Automated provisioning options include TR-069 and XML config files



TLS and SRTP security encryption technology to protect calls and accounts



4 WAY audio conferencing for easy conference calls

Protocols/Standards	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP, TR-069, 802.1x, TLS, SRTP
Network Interfaces	Dual switched auto-sensing 10/100/1000 Mbps Ethernet ports, integrated PoE
Graphic Display	132 x 64 backlit graphical LCD display
Feature Keys	3 line keys with dual-color LED and 3 SIP accounts, 3 XML programmable context sensitive soft keys, 5 (navigation, menu) keys, 8 BLF keys, 13 dedicated function keys for MUTE, HEADSET, TRANSFER, CONFERENCE, SEND and REDIAL, SPEAKERPHONE, VOLUME, PHONEBOOK, MESSAGE, HOLD, PAGE/INTERCOM, RECORD, HOME
Voice Codecs	Support for G.711 μ /a, G.722 (wide-band), G.723, G.726-32, G.729 A/B, iLBC, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC
Telephony Features	Hold, transfer, forward (unconditional/no-answer/busy), call park/pickup, 4-way conference, shared-call-appearance (SCA) / bridged-line-appearance (BLA), downloadable phone book (XML, LDAP, up to 500 items), call waiting, call history (up to 200 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones, server redundancy & fail-over
Headset Jack	RJ9 headset jack (allowing EHS with Plantronics headsets)
HD Audio	Yes, HD handset and speakerphone with support for wideband audio
Base Stand	Yes, 2 angled positions available, wall mountable
Wall Mountable	Yes
QoS	Layer 2 QoS (802.1Q, 802.1P) and Layer 3 QoS (ToS, DiffServ, MPLS)
Security	User and administrator level access control, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control
Multi-language	English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese and more
Upgrade/Provisioning	Firmware upgrade via TFTP / HTTP / HTTPS, mass provisioning using TR-069 or AES encrypted XML configuration file
Power and Green Energy Efficiency	Universal Power Supply Input 100-240VAC 50-60Hz; Output +5VDC, 600mAPoE: IEEE802.3 af Class 2, 3.84W-6.49W
Physical	Dimension: 222.5mm (L) x 208.5mm (W) x 76.2mm (H) (with handset) Unit weight: 0.8kg; Package weight: 1.2kg
Temperature and Humidity	Operation: 0°C to 40°C, Storage: -10°C to 60°C, Humidity: 10% to 90% Non-condensing
Package Content	GXP1630 phone, handset with cord, base stand, universal power supply, network cable, Quick Installation Guide, brochure, GPL License